



SINGLE GAS CLIP-ON PERSONAL MONITOR

Gas Detection For Life

01 Series



Features

- 4 Gases to choose from: LEL, CO, H₂S, or O₂
- Operates 3,000 hrs. on alkaline batteries (16 hours for LEL version)
- Pocket size 1.4"(W) x 4.1"(H) x 0.8"(D)
- Light weight 3.5 ounces
- Audible / visual / vibration alarms
- Automatic backlight during alarm
- Peak Hold, STEL & TWA
- Low battery alarm
- Impact and water resistant
- Intrinsically safe, CSA, C/US classified
- 2 year warranty

Applications

- Hazardous material
- Mining
- Refineries / petrochemical
- Water / wastewater treatment
- Pharmaceuticals
- Utilities
- Chemical plants
- Fire services

Individuals need personal protection in hazardous areas at all times without adding extra bulky equipment, and the 01 Series can provide that kind of protection at an affordable price. The GP-01, OX-01, CO-01, and HS-01 models are personal single gas monitors designed for personal protection from combustible hydrocarbons, oxygen deficiency, hydrogen sulfide, or carbon monoxide. Each model is controlled by a microprocessor for reliability and advanced capabilities. Each model can be operated continuously for at least 3,000 hours on (2) AAA size alkaline batteries except the GP-01, which operates for 16 hours. The 01 models have 2 preset alarms that are user adjustable and each version is also equipped with visual, audible, and vibration alarms as standard. The replacement sensors are inexpensive, easily field replaceable, have a life expectancy of 2 years, and are interchangeable with other RKI monitors such as the GX-2001, GX-2003, and GasWatch 2 models.

The entire 01 Series monitors are safe for use in hazardous locations, classified as intrinsically safe by CSA to U.S. and Canadian standards for Class I, Division 1, Groups A, B, C, and D atmospheres. For additional information please visit our web site at www.rkiinstruments.com.

* The GP-01 has an optional rechargeable battery pack.

01 Series

Model Name	OX-01	CO-01	HS-01	GP-01
Gas Detected	Oxygen (O2)	Carbon Monoxide (CO)	Hydrogen Sulfide (H2S)	Combustible gas
Detection Principle	Galvanic cell	Electrochemical		Catalytic combustion
Detection Range (Increments)	0 – 40%vol. (0.1% vol.)	0 – 500 ppm (1 ppm)	0 – 100 ppm (0.5 ppm)	0 – 100% LEL (1% LEL increments)
Alarm Set Points	Low 19.5% vol. High 23.5% vol. Over 40.0% vol.	1st 25 ppm 2nd 50 ppm TWA 25 ppm STEL 200 ppm Over 500 ppm	1st 10.0 ppm 2nd 30.0 ppm TWA 10.0 ppm STEL 15.0 ppm Over 100.0 ppm	1st 10% LEL 2nd 50% LEL Over 100% LEL
Alarm Types	Gas alarms: Trouble alarms:	1st and 2nd (user adjustable), OVER alarm, STEL and TWA Sensor connection, low battery circuit failure, and calibration range error		
Alarm Methods	Gas alarm: Trouble alarm: STEL & TWA alarms:	Flashing LED's, intermittent buzzer, flashing gas value, and vibration Flashing LED's, intermittent buzzer, and display of error message Flashing LED's, intermittent buzzer, flashing gas value, and vibration		
Gas Sampling	Diffusion			
Response Time	T90 in 20 seconds (Alarms within 5 seconds when exposed to 12% O2)	T90 in 30 seconds		
Accuracy which ever is greater	± 0.5% O2	± 5% of reading or ± 5 ppm CO	± 5% of reading or ± 2 ppm H2S	± 0.5% of reading or ± 2% LEL
Power	Alkaline dry cell (2-AAA size)			Alkaline dry cell Ni-Cad battery pack
Continuous Operation	Alkaline dry cell: more than 3,000 hours (at 25°C, no backlight)			Alkaline: 16 hours Ni-Cad: 8 hours
Safety Rating	CSA classified, "C/US", as intrinsically safe. Class I, Division 1, Groups A, B, C, D			
Dimensions & Weight	1.4"W x 4.1"H x 0.8"D, (35 x 105 x 20mm); 3.5 ounces (100g)			
Display	7-segment + symbol on digital LCD, auto backlighting during alarm			
Operating Temp. & Humidity	-4°F ~ 122°F (-20°C ~ 50°C); Humidity below 90% RH (non-condensing)			
Standard Accessories	• Rubber protective boots • Alkaline batteries		• Belt clip or alligator clip • Wrist strap	
Optional Accessories	• Calibration cap (adapter) • Calibration kit		• Charger unit (GP-01 only) • Ni-Cad battery pack (GP-01 only)	
Special Functions	• Manual backlight for LCD (automatically lit during alarm) • Peak hold, STEL & TWA			
Warranty	Two years material and workmanship			

Ordering Information:

OX-01, 0-40% O2 with alkaline and alligator clip.....	72-0008RK-01
OX-01, 0-40% O2 with alkaline and belt clip	72-0008RK-03
CO-01, 0-500 ppm with alkaline and alligator clip	73-0044RK-01
CO-01, 0-500 ppm with alkaline and belt clip	73-0044RK-03
HS-01, 0-100 ppm with alkaline and alligator clip.....	73-0046RK-01
HS-01, 0-100 ppm with alkaline and belt clip.....	73-0046RK-03
GP-01, 0-100% LEL with alkaline and alligator clip	73-0033RK-01
GP-01, 0-100% LEL with alkaline and belt clip.....	73-0033RK-03
GP-01, 0-100% LEL with Ni-Cad, 115 VAC charger, and alligator clip.....	72-0034RK-01
GP-01, 0-100% LEL with Ni-Cad, 115 VAC charger, and belt clip.....	72-0034RK-03
GP-01, 0-100% LEL with Ni-Cad battery pack, 12 VDC charger, and alligator clip	72-0034RK-04
GP-01, 0-100% LEL with Ni-Cad battery pack, 12 VDC charger, and belt clip	72-0034RK-05

Specifications subject to change without notice.



Toll Free: (800) 754-5165 • Phone: (510) 441-5656
Fax: (510) 441-5650 • www.rkiinstruments.com

Authorized Distributor: